



US008600553B2

(12) **United States Patent**
Svendsen et al.

(10) **Patent No.:** **US 8,600,553 B2**
(45) **Date of Patent:** **Dec. 3, 2013**

(54) **COVERAGE ROBOT MOBILITY**

(56) **References Cited**

(75) Inventors: **Selma Svendsen**, Andover, MA (US);
Daniel N. Ozick, Newton, MA (US);
Christopher M. Casey, Lexington, MA
(US); **Deepak Ramesh Kapoor**,
Cranston, RI (US); **Tony L. Campbell**,
Pepperell, MA (US); **Chikyung Won**,
Tewksbury, MA (US); **Christopher**
John Morse, Malden, MA (US); **Scott**
Thomas Burnett, Windham, NH (US)

U.S. PATENT DOCUMENTS

1,755,054 A 4/1930 Darst
1,780,221 A 11/1930 Buchmann
1,900,885 A 3/1933 Smellie

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2003275566 A1 6/2004
DE 21 28 842 12/1980

(Continued)

(73) Assignee: **iRobot Corporation**, Bedford, MA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1459 days.

OTHER PUBLICATIONS

PCT International Search Report, May 6, 2007.

(Continued)

(21) Appl. No.: **11/758,289**

(22) Filed: **Jun. 5, 2007**

Primary Examiner — Dalena Tran

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(65) **Prior Publication Data**

US 2008/0091305 A1 Apr. 17, 2008

Related U.S. Application Data

(63) Continuation of application No. 11/633,885, filed on
Dec. 4, 2006, now Pat. No. 7,441,298.

(60) Provisional application No. 60/741,442, filed on Dec.
2, 2005.

(51) **Int. Cl.**
B25J 19/02 (2006.01)

(52) **U.S. Cl.**
USPC **700/258; 318/580**

(58) **Field of Classification Search**
USPC 700/258, 245, 246, 249, 250, 256, 259,
700/261; 701/23, 25; 318/568.1, 568.12,
318/580, 581, 587, 567, 568.18; 901/1, 46,
901/47; 15/319

See application file for complete search history.

(57) **ABSTRACT**

An autonomous coverage robot includes a drive system, a bump sensor, and a proximity sensor. The drive system is configured to maneuver the robot according to a heading (turn) setting and a speed setting. The bump sensor is responsive to a collision of the robot with an obstacle in a forward direction. A method of navigating an autonomous coverage robot with respect to an object on a floor includes the robot autonomously traversing the floor in a cleaning mode at a full cleaning speed. Upon sensing a proximity of the object forward of the robot, the robot reduces the cleaning speed to a reduced cleaning speed while continuing towards the object until the robot detects a contact with the object. Upon sensing contact with the object, the robot turns with respect to the object and cleans next to the object, optionally substantially at the reduced cleaning speed.

25 Claims, 21 Drawing Sheets

